

Ecoflex® Thermal Twin Jr. with 5.5" Jacket

Submittal Information

Revision A: July 22, 2014

Project Information

Job Name:

Location: _____ Part No. Ordered: _____

Engineer: _____ Date Submitted: _____

Contractor: _____ Submitted By: _____

Manufacturer's Representative: _____ Approved By: _____

Technical Data

Service Pipe: Crosslinked polyethylene (PEX) SDR-9 Engel-method tubing that conforms to German DIN 4726; smoothness value of 0.02 mil; NSF-certified

Insulation: Multilayered, closed-cell, polyethylene-foam insulation with a thermal conductivity of 0.26 BTU in./sq. ft./hour/°F; vapor permeability of 0.1g/100 sq. in./day

Jacket: Corrugated seamless high-density polyethylene (HDPE); UV-protected

Hydrostatic Ratings: 200°F (93°C) at 80 psi (551 kPa or 5.51 bar)
180°F (82°C) at 100 psi (689 kPa or 6.89 bar)
73.4°F (23°C) at 160 psi (1102 kPa or 11.02 bar)



Product Information and Application Use

Uponor's Ecoflex® Thermal Twin Jr. is a pre-insulated pipe system for buried or aboveground commercial and residential hydronic radiant heating and cooling applications. Service pipes are made from durable Engel-method crosslinked polyethylene (PEX) pipe protected by multilayer polyethylene-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use with Uponor ProPEX® fittings or WIPEX™ dezincification-resistant (DZR) brass compression fittings.¹

✓ Description	Part Number	Service Pipe O.D.	Service Pipe I.D.	Foam Thickness	Insulation Value ²	Bend Radius	Weight (lbs./ft.)
1¼" Thermal Twin Jr. with 5.5" Jacket, 600-ft. coil	5025513	1.375"	1.054"	0.78"	R-5.09	28"	1.28 lbs.

Installation

Install Ecoflex Thermal Twin Jr. pre-insulated pipe in buried or aboveground hydronic radiant heating and cooling applications. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid groundwater contamination. For more information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.

Standards

ASTM F876, F877 and F1960; CSA B137.5; NSF/ANSI Standard 14 (NSF-rfh)

Codes

N/A

Listings

NSF/ANSI 14-certified

Related Applications

Pre-insulated Pipe Systems
Radiant Heating and Cooling Systems
Snow and Ice Melting Systems
Permafrost Prevention Systems
Turf Conditioning Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
www.uponorpro.com

Uponor Ltd.
2000 Argentia Road, Plaza 1, Suite 200
Mississauga, ON L5N 1W1 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
www.uponorpro.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.

²R-value is normalized based on the nominal foam thickness for a circular shape.