

Heat-trace End Seal, SF-E

Submittal information
Revision B: Oct. 2, 2018

Project information

Job name:	
Location:	Part no. ordered:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Materials:	Body: polyamide; conductors: nickel-coated brass
IP ratings:	Connector: IP66; end seal: IP67
Ambient temperature:	-40°F (-40°C) to 122°F (50°C)
Minimum operating temperature:	-85°F (-65°C)
Current rating:	16A continuous
Voltage range:	Up to 275V



Product information and application use

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.

✓ Description	Part no.	Length	Width	Height	Weight
Heat-trace End Seal, SF-E	5993000	2.17" (55mm)	1.22" (31mm)	0.87" (22mm)	0.05 lbs. (24g)

Installation

Simply cut back one wire ¼" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.

Listings

ATEX Sira 04ATEX3293X, Sira 05ATEX3099U; IECEX SIR 11.0136U

Related applications

Pre-insulated pipe systems
Permafrost prevention systems
PEX-a plumbing systems

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
uponorpro.com
uponorengineering.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
uponorpro.com
uponorengineering.com