

uponor



ProPEX® Lead-free (LF) Brass Commercial Ball Valves

Industry-first LF Brass Commercial Ball Valves



www.uponorpro.com



- LF brass PEX-to-PEX, full-port valve
- Available in sizes from ½" to 2"
- ASTM F1960, NSF 14/61, NSF 359 and U.P. Code listed
- Blow-out proof stem
- Stem extension kits for insulated piping applications (accommodates up to 2" of insulation)
- 100% visual ProPEX® connection; cannot be dry fit
- Meets NSF 359 valve standard referenced in 2015 IPC; no other valve currently meets this requirement



Part No.	Part Description
LFC4825050	ProPEX LF Brass Commercial Ball Valve, (full port), ½" PEX x ½" PEX
LFC4827575	ProPEX LF Brass Commercial Ball Valve, (full port), ¾" PEX x ¾" PEX
LFC4821010	ProPEX LF Brass Commercial Ball Valve, (full port), 1" PEX x 1" PEX
LFC4821313	ProPEX LF Brass Commercial Ball Valve, (full port), 1¼" PEX x 1¼" PEX
LFC4821515	ProPEX LF Brass Commercial Ball Valve, (full port), 1½" PEX x 1½" PEX
LFC4822020	ProPEX LF Brass Commercial Ball Valve, (full port), 2" PEX x 2" PEX
F5630001	Stem Extension Kit for ½" and ¾" Valves
F5630002	Stem Extension Kit for 1" and 1¼" Valves
F5630003	Stem Extension Kit for 1½" and 2" Valves