

# Engineered Polymer (EP) Branch Opposing-port Multi-port Tee

Submittal Information  
Revision D: Feb. 1, 2016

## Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:

Approved By:

## Technical Data

Material:	Polysulfone GF120
Maximum Temperature (no pressure):	320°F (160°C)
Maximum Working Temperature/Pressure:	210°F (99°C) at 150 psi
Maximum Multi-port Tee Flow for ¾" Inlet:	13.2 gpm at 12 fps 8.8 gpm at 8 fps



## Product Information and Application Use

Engineered Polymer (EP) Branch Opposing-port Multi-port Tee features a ¾" ProPEX® inlet with opposing ½" ProPEX branch outlets.<sup>1</sup> These are designed for central location to facilitate piping in two directions. The tee is made of EP, which is proven in demanding hot-water applications.

✓ Description	Part Number	Length	Height	Width	Weight
¾" EP Branch Opposing-port Multi-port Tee, 3 outlets	Q2337550	3.58"	2.38"	1.18"	0.066 lbs.
¾" EP Branch Opposing-port Multi-port Tee, 4 outlets	Q2347550	3.58"	2.38"	1.18"	0.071 lbs.
¾" EP Branch Opposing-port Multi-port Tee, 8 outlets	Q2387550	6.08"	2.38"	1.18"	0.135 lbs.

## Installation

Use any product designed to mount 1" copper pipe as a mounting bracket. For more information, refer to the Uponor AquaPEX® Professional Plumbing Installation Guide.

## Standards

CAN/CSA B137.5; ASTM F877; ASTM F1960

## Codes

IPC; UPC; NSPC; NPC of Canada

## Listings

ANSI/NSF 14- and 61-certified; ICC ESR 1099; IAPMO 3946, cQALus P321

## Related Applications

PEX-a Plumbing Systems

## Contact Information

Uponor, Inc.  
5925 148<sup>th</sup> Street West  
Apple Valley, MN 55124 USA  
Phone: 800.321.4739  
Fax: 952.891.2008  
www.uponorpro.com

Uponor Ltd.  
2000 Argentia Road, Plaza 1, Suite 200  
Mississauga, ON L5N 1W1 CANADA  
Phone: 888.994.7726  
Fax: 800.638.9517  
www.uponorpro.com

<sup>1</sup>ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.