

Engineered Polymer (EP) Branch Opposing-port Multi-port Tee

Submittal Information
Revision E: July 23, 2019

Project information

Job name:

Location:

Part no. ordered:

Engineer:

Date submitted:

Contractor:

Submitted by:

Manufacturer's representative:

Approved by:

Technical data

Material: Engineered polymer (EP)
Maximum temperature (no pressure): 320°F (160°C)
Maximum working temperature/pressure: 210°F (99°C) at 150 psi
Maximum multi-port tee flow for ¾" inlet: 13.2 gpm at 12 fps; 8.8 gpm at 8 fps

Product information and application use

Engineered polymer (EP) branch opposing-port multi-port tees feature a ¾" ProPEX® inlet with opposing ½" ProPEX branch outlets.¹ These are designed for a central location to facilitate piping in two directions.



✓ Description	Part number	Length	Height	Width	Weight
¾" EP Branch Opposing-port Multi-port Tee, 3 outlets	Q2337550	3.58"	2.38"	1.18"	0.066 lbs.
¾" EP Branch Opposing-port Multi-port Tee, 4 outlets	Q2347550	3.58"	2.38"	1.18"	0.071 lbs.
¾" EP Branch Opposing-port Multi-port Tee, 8 outlets	Q2387550	6.08"	2.38"	1.18"	0.135 lbs.

Installation

Use any product designed to mount 1" copper pipe as a mounting bracket. For more information, refer to the Uponor Piping Systems Installation Guide.

Standards

ASTM E84; ASTM E119; ASTM E814; ASTM F877; ASTM F1960; CAN/CSA B137.5; NSF 14; NSF 61

Codes

IBC; IMC; IPC; IRC; NPC of Canada; NSPC; UMC; UPC

Listings

cNSFus-pw; cQAlus P321; HUD MR 1269; ICC-ES-PMG-1006; ICC-ES-PMG-1012; U.P. Code

Related applications

PEX-a plumbing systems

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
uponorpro.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.