

Engineered Polymer (EP) Flow-through Opposing-port Multi-port Tee

Submittal information

Revision E: July 23, 2019

Project information

Job name:

Location:

Part no. ordered:

Engineer:

Date submitted:

Contractor:

Submitted by:

Manufacturer's representative:

Approved by:

Technical data

Material:	Engineered polymer (EP)
Maximum temperature (no pressure):	320°F (160°C)
Maximum working temperature/pressure:	210°F (99°C) at 150 psi
Maximum multi-port tee flow for ¾" inlet:	13.2 gpm at 12 fps; 8.8 gpm at 8 fps



Product information and application use

Engineered polymer (EP) flow-through opposing-port multi-port tees feature ¾" ProPEX® inlets with opposing ½" ProPEX branch outlets.¹ The tees are designed for central location to facilitate piping in two directions.

✓ Description	Part number	Length	Height	Width	Weight
EP Flow-through Opposing-port Multi-port Tee, 3 outlets, ¾" x ¾" ProPEX	Q2337557	4.41"	2.38"	1.18"	0.072 lbs.
EP Flow-through Opposing-port Multi-port Tee, 4 outlets, ¾" x ¾" ProPEX	Q2347557	4.41"	2.38"	1.18"	0.077 lbs.
EP Flow-through Opposing-port Multi-port Tee, 6 outlets, ¾" x ¾" ProPEX	Q2367557	5.66"	2.38"	1.18"	0.108 lbs.

Installation

Use any product designed to mount 1" copper pipe as a mounting bracket. For more information, refer to the Uponor AquaPEX® Professional Plumbing Installation Guide.

Standards

ASTM E84; ASTM E119; ASTM E814; ASTM F877; ASTM F1960; CAN/CSA B137.5; NSF 14; NSF 61

Codes

IBC; IMC; IPC; IRC; NPC of Canada; NSPC; UMC; UPC

Listings

cNSFus-pw; cQAlus P321; HUD MR 1269; ICC-ES-PMG-1006; ICC-ES-PMG-1012; U.P. Code

Related applications

PEX-a plumbing systems

Contact information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
uponorpro.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.