

## ProPEX® Lead-free (LF) Brass Ball Valve

Submittal information  
Revision I: Oct. 29, 2019

### Project information

Job name:

Location:

Part no. ordered:

Engineer:

Date submitted:

Contractor:

Submitted by:

Manufacturer's representative:

Approved by:

### Technical data

Material:	C69300 brass
Maximum temperature (no pressure):	200°F (93.3°C)
Maximum working pressure:	200 psi (13.8 bar)

### Product information and application use

Use Uponor ProPEX® lead-free (LF) brass ball valves in all plumbing and radiant heating/cooling applications.<sup>1</sup>

Both ends are manufactured with the ProPEX fitting for connections to Uponor AquaPEX® or Wirsbo hePEX™ tubing.

**Note:** These valves are not compatible with applications using glycol.



✓	Description	Part number	Length	Width	Weight	Cv
	ProPEX LF Brass Ball Valve, ½" PEX x ½" PEX	LF4815050	2¾"	1½"	0.18 lbs.	4.0
	ProPEX LF Brass Ball Valve, ¾" PEX x ¾" PEX	LF4817575	3"	1¾"	0.32 lbs.	6.1

### Installation

Install valves according to local building code. Do not dismantle. Refer to the Uponor Piping Systems Installation Guide or the Uponor Radiant Floor Heating Installation Handbook for additional information.

### Standards

ASTM F1960; ASTM F877; CSA B137.5; NSF-359

### Codes

IPC; UPC; NPC of Canada

### Listings

NSF-14; NSF-61: U.P. Code; NSF-372; NSF-359

### Related applications

PEX-a plumbing systems  
Radiant heating and cooling systems

### Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124 USA  
T 800.321.4739  
F 952.891.2008  
uponorpro.com

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4 CANADA  
T 888.994.7726  
F 800.638.9517  
uponorpro.com

<sup>1</sup>ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.