

## ProPEX® Lead-free (LF) Brass Commercial Ball Valve

Submittal information

Revision D: March 12, 2020

### Project information

Job name:

Location:

Part no. ordered:

Engineer:

Date submitted:

Contractor:

Submitted by:

Manufacturer's representative:

Approved by:

### Technical data

Material (body, ball and stem): Lead-free (LF) brass

Cold working pressure (CWP): 250 psi

### Product information and application use

Use Uponor ProPEX® Lead-free Brass Commercial Ball Valves for all commercial PEX piping applications.<sup>1</sup> Both ends are manufactured with the ProPEX fitting for direct connections to Uponor PEX piping.

**Note:** These valves are compatible with applications using a propylene glycol mixture up to a maximum of 50% propylene glycol.



✓ Description	Part number	Length	Width	Weight	Cv
ProPEX LF Brass Commercial Ball Valve (full port), ½" PEX x ½" PEX	LFC4825050	2.75"	0.92"	0.36 lbs.	7.0
ProPEX LF Brass Commercial Ball Valve (full port), ¾" PEX x ¾" PEX	LFC4827575	3.25"	1.28"	0.52 lbs.	18.7
ProPEX LF Brass Commercial Ball Valve (full port), 1" PEX x 1" PEX	LFC4821010	4.27"	1.81"	1.3 lbs.	29.0
ProPEX LF Brass Commercial Ball Valve (full port), 1¼" PEX x 1¼" PEX	LFC4821313	4.75"	1.81"	1.44 lbs.	54.7
ProPEX LF Brass Commercial Ball Valve (full port), 1½" PEX x 1½" PEX	LFC4821515	5.68"	2.07"	2.12 lbs.	68.2
ProPEX LF Brass Commercial Ball Valve (full port), 2" PEX x 2" PEX	LFC4822020	7.125"	2.84"	4.18 lbs.	132.2
Stem Extension Kit for ½" and ¾" Valves	F5630001	2.625"	0.906"	0.31 lbs.	N/A
Stem Extension Kit for 1" and 1¼" Valves	F5630002	2.625"	1.063"	0.48 lbs.	N/A
Stem Extension Kit for 1½" and 2" Valves	F5630003	2.625"	1.26"	0.57 lbs.	N/A

### Installation

Install valve and stem extension kit according to local building code. Do not dismantle. Refer to the Uponor Piping Systems Installation Guide or the Uponor Plumbing Design Assistance Manual (PDAM) for additional information.

### Standards

CSA B137.5; ASTM F877; ASTM F1960; NSF-359

### Codes

IPC; UPC; NSPC; NPC of Canada

### Listings

ANSI/NSF 14- and 61-certified; U.P. Code, Annex G, NSF-359

### Related applications

PEX-a plumbing systems  
 Radiant heating and cooling systems  
 Snow and ice melting systems  
 Permafrost protection systems  
 Turf conditioning systems

### Contact information

Uponor, Inc.  
 5925 148<sup>th</sup> Street West  
 Apple Valley, MN 55124 USA  
 Phone: 800.321.4739  
 Fax: 952.891.1409  
 uponorpro.com  
 uponorengineering.com

Uponor Ltd.  
 6510 Kennedy Road  
 Mississauga, ON L5T 2X4 CANADA  
 Phone: 888.994.7726  
 Fax: 800.638.9517  
 uponorpro.com  
 uponorengineering.com

<sup>1</sup>ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.