

Pre-insulated Uponor AquaPEX® with ½" Insulation, Straight Lengths

Submittal Information
Revision I: Sept. 18, 2018

Project information

Job Name:	
Location:	Part No. ordered:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Service Pipe:	Crosslinked polyethylene (PEX-a) Engel-method tubing encased in ½" PEX-foam insulation; PEX 5106
Insulation:	Multi-layer, closed-cell, crosslinked polyethylene foam
Thermal conductivity:	0.250 Btu.in/sq.ft.h.degF
Operating condition limits: (hydrostatic ratings)	200°F (93°C) at 80 psi (551 kPa) 180°F (82°C) at 100 psi (689 kPa) 73.4°F (23°C) at 160 psi (1,103 kPa) ½", ¾", 1", 1¼", 1½" and 2" Uponor AquaPEX® White only: 120°F (49°C) at 130 psi (896 kPa)
Linear expansion rate:	1.10"/10°F/100' (27.94mm/5.56°C/30.48m)



Product information and application use

Pre-insulated Uponor AquaPEX® tubing offers all the benefits of Uponor AquaPEX — durable, flexible, corrosion-resistant — encased in ½" PEX-foam insulation for the additional benefit of insulating potable-water lines and meeting national, state and local energy codes. The tubing is approved for use in hot and cold domestic potable water systems, residential fire safety and hydronic radiant heating and cooling systems containing no ferrous corrodible components or where ferrous components are isolated from the tubing. This product is approved for direct-burial applications in soil or concrete.

✓ Description	Part no.	O.D.	Heat loss (at 70° Delta T)	R-Value	Weight (per bundle)
1¼" Pre-insulated Uponor AquaPEX with ½" insulation, 20-ft. straight length, 100 ft. (5 per bundle)	F6921250	2.53"	15.2 BTU/h/ft	2.9	38.3 lbs.
1½" Pre-insulated Uponor AquaPEX with ½" insulation, 20-ft. straight length, 100 ft. (5 per bundle)	F6921500	2.78"	17.1 BTU/h/ft	2.8	47.8 lbs.
2" Pre-insulated Uponor AquaPEX with ½" insulation, 20-ft. straight length, 100 ft. (5 per bundle)	F6922000	3.28"	21.0 BTU/h/ft	2.7	72.6 lbs.

Installation

Approved fitting system is ProPEX®.¹ Refer to the ProPEX Connections Instructional Guide, Uponor Piping Pocket Guide, Plumbing Design Assistance Manual (PDAM), Complete Design Assistance Manual (CDAM), Hydronic Piping Design Assistance Manual (HPDAM) or AquaSAFE™ Residential Fire Sprinkler Installation Guide for more information.

Listings²

cNSFus-fs³; cNSFus-pw; cQAlus⁵; UL; CSA; PPI TR-4; ICC-ES; IAPMO; BMEC; CCMC

Codes

ICC; IPC; IMC; IRC; UPC; UMC; NSPC; HUD; UFGS; NPC of Canada; NBC of Canada

Standards

ANSI/NSF 14; ANSI/NSF 61; ASTM F876; ASTM F877; ASTM F1960; ASTM F2023; ASTM E84⁵; CAN/ULC S102.2⁵; ASTM E119/UL 263; CAN/ULC S101; ASTM E814/ULC S115; AWWA C904⁴; CSA B137.5; CSA B214; UL 1821³; ULC/ORD-C199P³

Related applications

PEX-a plumbing systems
Radiant heating and cooling systems
AquaSAFE™ fire safety systems
Hydronic piping systems

Contact information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
uponorpro.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.; ²Visit listing agency's website for complete information; ³For ¾", 1" and 1¼" tubing only; ⁴For ¾" tubing and larger; ⁵See listings/standards for un-insulated Uponor AquaPEX.