

ProPEX® Lead-free (LF) Brass to Copper Ball Valve

Submittal information
Revision G: Oct. 29, 2019

Project information

Job name:	
Location:	Part no. ordered:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material:	C69300 brass
Maximum working temperature:	200°F (93.3°C)
Maximum working pressure:	200 psi (13.8 bar)



Product information and application use

Uponor ProPEX® lead-free (LF) brass ball valves transition brass to copper and feature in-line isolation valves.¹ These valves are not compatible with applications using glycol.

✓ Description	Part number	Length	Height	Weight	Cv
ProPEX LF Brass Ball Valve, ½" PEX x ½" Copper Adapter	LF4805050	2⅞"	1½"	0.18 lbs.	3.9
ProPEX LF Brass Ball Valve, ¾" PEX x ¾" Copper Adapter	LF4807575	3"	1¾"	0.32 lbs.	6.6

Installation

Install valve according to local building code. Do not dismantle. If soldering, aim flame away from the fitting. For more information, refer to the Uponor Piping Systems Installation Guide or the Radiant Floor Heating Installation Handbook.

Standards

ASTM F1960; ASTM F877; CSA B137.5; NSF-359

Codes

UPC; NPC of Canada

Listings

NSF-14; NSF-61: U.P. Code; NSF-372; NSF-359

Related applications

PEX-a plumbing systems
Radiant heating and cooling systems
Snow and ice melting systems
Permafrost protection systems
Turf conditioning systems

Contact information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
T 800.321.4739
F 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
T 888.994.7726
F 800.638.9517
uponorpro.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.