

ProPEX® Lead-free (LF) Brass Ball Valve

Submittal information
Revision G: Feb. 15, 2019

Project information

Job name:

Location:

Engineer:

Contractor:

Manufacturer's representative:

Part no. ordered:

Date submitted:

Submitted by:

Approved by:

Technical data

Material:	C69300 brass
Maximum temperature (no pressure):	200°F (93.3°C)
Maximum working pressure:	200 psi (13.8 bar)

Product information and application use

Use Uponor ProPEX® lead-free (LF) brass ball valves in all plumbing and radiant heating/cooling applications.¹

Both ends are manufactured with the ProPEX fitting for connections to Uponor AquaPEX® or Wirsbo hePEX™ tubing.

Note: These valves are not compatible with applications using glycol.



✓	Description	Part number	Length	Width	Weight	Cv
	ProPEX LF Brass Ball Valve, ½" PEX x ½" PEX	LF4815050	2¾"	1½"	0.18 lbs.	7.17
	ProPEX LF Brass Ball Valve, ¾" PEX x ¾" PEX	LF4817575	3"	1¾"	0.32 lbs.	10.7

Installation

Install valves according to local building code. Do not dismantle. Refer to the Uponor AquaPEX Professional Plumbing Installation Guide or the Uponor Radiant Floor Heating Installation Handbook for additional information.

Standards

ASTM F1960; ASTM F877; CSA B137.5; NSF-359

Codes

UPC; NPC of Canada

Listings

NSF-14; NSF-61: U.P. Code; NSF-372; NSF-359

Related applications

PEX-a plumbing systems
Radiant heating and cooling systems

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
T 800.321.4739
F 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
T 888.994.7726
F 800.638.9517
uponorpro.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.