

## ProPEX® Lead-free (LF) Brass Ball Valve

Submittal information  
Revision F: June 26, 2018

### Project information

Job name:

Location:

Part no. ordered:

Engineer:

Date submitted:

Contractor:

Submitted by:

Manufacturer's representative:

Approved by:

### Technical data

Material:	C69300 brass
Maximum temperature (no pressure):	200°F (93.3°C)
Maximum working pressure:	200 psi (13.8 bar)

### Product information and application use

Use Uponor ProPEX® lead-free (LF) brass ball valves in all plumbing and radiant heating/cooling applications.<sup>1</sup>

Both ends are manufactured with the ProPEX fitting for connections to Uponor AquaPEX® or Wirsbo hePEX™ tubing.

**Note:** These valves are not compatible with applications using glycol.



✓	Description	Part number	Length	Width	Weight	Cv
	ProPEX LF Brass Ball Valve, ½" PEX x ½" PEX	LF4815050	2¾"	1½"	0.18 lbs.	7.17
	ProPEX LF Brass Ball Valve, ¾" PEX x ¾" PEX	LF4817575	3"	1¾"	0.32 lbs.	10.7

### Installation

Install valves according to local building code. Do not dismantle. Refer to the Uponor AquaPEX Professional Plumbing Installation Guide or the Uponor Radiant Floor Heating Installation Handbook for additional information.

### Standards

ASTM F1960; ASTM F877; CSA B125.3; CSA B137.5; NSF-359

### Codes

UPC; NPC of Canada

### Listings

NSF-14; NSF-61: U.P. Code; NSF-372

### Related applications

PEX-a plumbing systems  
Radiant heating and cooling systems

### Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124 USA  
T 800.321.4739  
F 952.891.2008  
uponorpro.com

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4 CANADA  
T 888.994.7726  
F 800.638.9517  
uponorpro.com

<sup>1</sup>ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.