

Straight Insulation Kit

Submittal information

Revision B: Jan. 22, 2020

Project information

Job name:

Location:

Part no. ordered:

Engineer:

Date submitted:

Contractor:

Submitted by:

Manufacturer's representative:

Approved by:

Technical data

Straight insulation kit, half shell:	Acrylonitrile butadiene styrene (ABS) thermoplastic polymer
Seal adhesive cartridge:	Bostik 2639
Body-bound rivets:	Plastic
Hexagonal screws:	Stainless steel, 13 mm hex head, 45 mm length
Hexagonal nuts:	Stainless steel, 13 mm



Product information and application use

Straight insulation kits make an insulated straight connection of single or twin-style pre-insulated pipe products with a jacket size of 5.5", 6.9" and 7.9". The kit features two shells, stainless-steel bolts, plastic pins and joint-sealing compound. Use with Uponor rubber end caps only.

✓	Description	Part number	Jacket size		Height	Length	Width	Weight
			(mm)	(in)				
	Straight Insulation Kit	1021992	140 mm	5.5"	8"	47"	11"	14 lbs.
			175 mm	6.9"	8"	47"	11"	14 lbs.
			200 mm	7.9"	8"	47"	11"	14 lbs.

Installation

If needed, install reducing sockets before couplings. Conduct hydraulic pressure test after installing couplings. Use Ecoflex rubber end caps (required) at all ends of the piping system to ensure insulation integrity. Refer to the Ecoflex Insulation Kits Instruction Sheet for further information.

Standards

N/A

Codes

N/A

Listings

N/A

Related applications

Pre-insulated pipe systems
PEX-a plumbing systems (Canada only)

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
uponorpro.com