

ProPEX® Engineered Polymer (EP) Opposing-port Tee

Submittal information
Revision B: June 5, 2019

Project information

Job name:	
Location:	Part no. ordered:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material:	Engineered polymer
Maximum temperature (no pressure):	320°F (160°C)
Maximum working temperature/pressure:	210°F (99°C) at 150 psi

Product information and application use

ProPEX® engineered polymer (EP) opposing-port tees feature 1" through 2" ProPEX flow-through connections with opposing ¾" ProPEX branch outlets.¹



✓ Description	Part number	Cv through	Cv branch	Length	Height	Width	Weight
ProPEX EP Opposing-port Tee, 1" x 1" x ¾" x ¾"	Q4801075	34.1	8.9	4.13"	3.31"	1.48"	0.095 lbs.
ProPEX EP Opposing-port Tee, 1¼" x 1¼" x ¾" x ¾"	Q4801375	57.1	9.1	4.71"	3.41"	1.82"	0.123 lbs.
ProPEX EP Opposing-port Tee, 1½" x 1½" x ¾" x ¾"	Q4801575	69.3	9.0	5.43"	3.71"	2.07"	0.173 lbs.
ProPEX EP Opposing-port Tee, 2" x 2" x ¾" x ¾"	Q4802075	130.0	9.1	6.41"	4.00"	2.82"	1.322 lbs.

Installation

Use the appropriate ProPEX ring for PEX piping. Refer to the Uponor Piping Pocket Guide or the Uponor Hydronic Piping Design Assistance Manual (HPDAM) for additional information.

Standards

ASTM E84; ASTM E119; ASTM E814; ASTM F877; ASTM F1960; CAN/CSA B137.5; NSF 14; NSF 61

Codes

IBC; IMC; IPC; IRC; NPC of Canada; NSPC; UMC; UPC

Listings

cNSFus-pw; cNSFus-rfh; cQAIus P321; HUD MR 1269; ICC-ES-PMG-1006; ICC-ES-PMG-1012; U.P. Code

Related applications

Hydronic radiant heating and cooling systems

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
uponorpro.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.