

End Cap with Vent, R32

Submittal information
Revision C: Feb. 3, 2020

Project information

Job name:	
Location:	Part no. ordered:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material:	UNS C3850 brass
Maximum working pressure:	145 psi
Maximum temperature/flow:	220°F (104°C)/21.0 gpm
Connection:	1¼" BSP

Product information and application use

The End Cap with Vent, R32, caps the end of the TruFLOW™ Jr. modular manifolds. It comes complete with a swivel drain valve and a manual air vent. Includes required Manifold Gasket (A2403232).



✓ Description	Part number	Dimensions			Weight
		Length	Width	Height	
End Cap with Vent, R32	A2803250	2.75"	1.75"	3.50"	0.9 lbs.
Manifold Gasket, spare part	A2403232	O.D. 1.55"	I.D. 1.24"	Thickness 0.093"	0.005 lbs.

Installation

Use with TruFLOW Jr. modular manifolds (not preassembled). Use the End Cap with Vent on the top manifold, following procedures outlined in the Uponor TruFLOW Jr. instruction sheet.

Standards

ISO 228-G 1¼" BSP

Codes

UMC; IMC; IRC; NPC of Canada

Listings

N/A

Related applications

Radiant heating and cooling systems

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
Uponorpro.com