

TruFLOW™ Classic Manifold Offset Union

Submittal information
Revision C: Jan. 14, 2020

Project information

Job name:

Location:

Part no. ordered:

Engineer:

Date submitted:

Contractor:

Submitted by:

Manufacturer's representative:


Approved by:

Technical data

Material: UNS C3850 brass
Maximum working pressure: 145 psi
Maximum temperature: 220°F (104°C)
Connection: 1¼" male BSP x R32

Product information and application use

TruFLOW™ classic manifold offset unions feature an R32 union by 1¼" BSP male connection for easy alignment of the supply and return piping at the manifold.



✓ Description

TruFLOW Classic Manifold Offset Union, R32 Union x 1¼" BSP

Part Number

A2620045

A

2.96"

B

2.30"

Weight

0.60 lbs.

Installation

Use the TruFLOW Classic Manifold Offset Union to make the connection between TruFLOW manifolds and R32 manifold adapters. Remove the existing straight union assembly from the manifold to install this offset union. Use silicone oil on the male threads to ease installation. Use only the following Uponor TruFLOW manifold accessories: Replacement O-ring for 1¼" BSP Connections (A2620008) and Replacement Gasket for R32 Union Connections (A2620005). For more information, refer to the Uponor TruFLOW Classic Manifold Instruction Sheet.

Standards

ISO 228-G 1¼" BSP

Codes

UMC; IMC; IRC; NPC of Canada

Listings

N/A

Related applications

Radiant heating and cooling systems

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
uponorpro.com