



Uponor PEX Approved for Commercial Applications in North Carolina Plumbing Code

Uponor crosslinked polyethylene (PEX) tubing is approved for use in commercial applications in the International Code Council (ICC) International Plumbing Code (IPC).

Section 308, Piping Support

- Table 308.5, Hanger Spacing, states, "Crosslinked polyethylene (PEX) pipe has a maximum horizontal spacing of 32 inches and a maximum vertical spacing of 10 feet."

Section 605, Materials, Joints and Connections

- Table 605.3, Water Service Pipe, states "Crosslinked polyethylene (PEX) plastic tubing meets standards ASTM F876, ASTM F877 and CSA B137.5."
- Table 605.4, Water Distribution Pipe, states "Crosslinked polyethylene (PEX) plastic tubing meets standards ASTM F877 and CSA B137.5."
- Table 605.5, Pipe Fittings, states, "Fittings for crosslinked polyethylene (PEX) plastic tubing meet ASTM F1807, ASTM F1960 and ASTM F2080."
- Section 605.17.2, Mechanical Joints, states, "Fittings for crosslinked polyethylene (PEX) plastic tubing as described in ASTM F1807, ASTM F1960 and ASTM F2080 shall be installed in accordance with the manufacturer's instructions."



For more information, visit www.uponorpro.com

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Tel: 800.321.4739
Fax: 952.891.2008
Web: www.uponor-usa.com

Uponor Ltd.
2000 Argentia Rd., Plaza 1, Ste. 200
Mississauga, ON L5N 1W1 CANADA
Tel: 888.994.7726
Fax: 800.638.9517
Web: www.uponor.ca