



PLUMBING SYSTEMS

PROPEX™  
OUT-OF-THE-WALL  
SUPPORT SYSTEM

FREQUENTLY  
ASKED QUESTIONS

## FAQs: ProPEX™ Out-of-the-Wall Support System

### What components make up the new ProPEX™ Out-of-the-Wall Support System?

The new ProPEX™ Out-of-the-Wall Support System includes a ProPEX Wall Support Bracket with alternating 1/2-inch and 3/4-inch holes, a 1/2" Plastic Bend Support, and a ProPEX Escutcheon in chrome or white finish for 1/2" crosslinked polyethylene (PEX) tubing.

### Why is the Out-of-the-Wall Support System approach better?

The Out-of-the-Wall Support System makes it easier to exit a wall with a solid support and a clean, finished look. It provides a more efficient, attractive and secure transition from PEX to fixtures, while totally eliminating the need to put in copper stub-outs behind the wall.

### How does it work?

The Plastic Bend Support snaps into the Wall Support Bracket to provide rigid positioning for 1/2" PEX from any angle. Use either the white or chrome-plated escutcheon with its mating sleeve to entirely conceal the wall penetration and ProPEX connection outside the wall. The flared escutcheons allow ProPEX expansions with the sleeve in

place; and for 3/4" PEX, just use the Wall Support Bracket for straight-through access.

### What are the savings for the installer?

The ProPEX Out-of-the-Wall Support System reduces installation time by eliminating the need for behind-the-wall connections and transition fittings, as compared with copper stub-outs. In addition, the

ProPEX Wall Support Bracket quickly mounts across stud spaces and features 2" on-center 1/2" and 3/4" built-in openings that simplify the task of locating the valves.

### Can the ProPEX Out-of-the-Wall Support System be used in any wall?

Yes. The 18" Wall Support Bracket is designed to be easily mounted across a 16" or smaller stud space.

