

H-insulation Kit

Submittal Information
Revision A: July 28, 2008

Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:

Approved By:

Technical Data

Material:

H-insulation Kit 2X (140-175-200), Half Shell:	ABS (thermoplastic material made of acrylonitrile, butadiene and styrene)
Seal Adhesive Cartridge:	Bostik 2639
Body-bound Rivets:	Plastic
Metal Sheets:	Stainless steel (1.4301)
Hexagonal Screws:	Stainless steel A2/70, M8x40, SW 13, DIN 933
Hexagonal Nuts:	Stainless steel A2, M8, DIN 934



Product Information and Application Use

The H-insulation Kit makes an insulated H-connection between single and twin-style pre-insulated pipe products with a jacket size of 5.5", 6.9" and 7.9". The kit features two shells, stainless steel bolts, plastic pins and joint-sealing compound. Use with Uponor Rubber End Caps only.

✓	Description	Part Number	Jacket Size		Height	Width	Length	Weight
			(mm)	(inch)				
[]	H-insulation Kit	1007355	140mm	5.5"	24"	50"	51"	42 lbs.
[]			175mm	6.9"	24"	50"	51"	42 lbs.
[]			200mm	7.9"	24"	50"	51"	42 lbs.

Installation

If needed, install reducing sockets before couplings. Conduct hydraulic pressure test after installing couplings. Use End Caps (required) at all ends of the piping system to ensure insulation integrity. Refer to the Insulation Kit Mounting Instructions.

Standards

N/A

Codes

N/A

Listings

N/A

Related Applications

Pre-Insulated Pipe Systems
PEX-a Plumbing Systems (Canada only)

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN
55124 USA
Phone: (800) 321-4739
Fax: (952) 891-2008
www.uponor-usa.com

Uponor Ltd.
655 Park Street
Regina, SK S4N 5N1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca