

ASTM Ecoflex® Rubber End Cap, Twin

Submittal information

Revision C: May 15, 2017

Project information

Job name:

Location:

Part no. ordered:

Engineer:

Date submitted:

Contractor:

Submitted by:

Manufacturer's representative:

Approved by:

Technical data

Material:

Rubber end cap: EPDM (ethylene propylene diene monomer) rubber

Clamp device: Stainless steel

O-ring: EPDM rubber

Product information and application use

ASTM Ecoflex® rubber end caps seal the exposed insulation between the jacket and service pipe when cutting pipe to make a connection. Designed to support system integrity, Ecoflex end caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination.



✓	Description	Part number	Jacket size (mm)	Jacket size (inches)	Length	Weight	Compatible pipes
	Twin End Cap, 1", 1¼" and 1½" PEX Pipe with 6.9" Jacket	5956915	175mm	6.9"	3.5"	1.0 lbs.	5026910, 5026913, 5026915, 5226910, 5226913, 5226515
	Twin End Cap, 2" and 2½" PEX Pipe with 7.9" Jacket	5957925	200mm	7.9"	3.5"	1.0 lbs.	5027920, 5027925, 5227920

Installation

End caps includes an O-ring and clamp device for a water-tight installation. Slip end caps on the jacket pipe and ensure that the O-ring stays in place. Refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual for more information.

Standards

N/A

Codes

N/A

Listings

N/A

Related applications

Pre-insulated pipe systems
Radiant heating and cooling systems
Snow and ice melting systems
Permafrost prevention systems
Turf conditioning systems

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
T 800.321.4739
F 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
T 888.994.7726
F 800.638.9517
uponorpro.com