

5925 148th Street West Apple Valley, MN 55124 Phone: 800-321-4739 Fax: 952-891-1409

1" Copper Manifold with 1/2" Outlets

Submittal Information

Component


www.wirsbo.com

Dra	. ^ ^ +	Into	rm	atior
	-			<i>au.</i>

Job Name:	Part No. Ordered:
Location:	Quantity Ordered:
	P.O. Number:
Engineer:	Date Submitted:
Contractor:	Submitted By:
Mfg Rep:	Approved By:

Technical Data

Material	Type L Copper
Max Temp (no pressure)	320°F
Max Use Temp/Pressure	210°F @ 150 psi
Max Manifold Flow @ 5 fps	12.8 gpm
Max Manifold Flow @ 8 fps	20.5 gpm



Product Information and Application Use

The Wirsbo Copper Valved Manifold is used for hot and cold domestic potable water distribution systems. The

manifold has a 1" copper sweat fitting adapter supply connection. All outlets are configured with 1/2" brass ProPEX connections.

Ordering Information

D	im	en	ISİ	o	n	al	1	n	t	O	r	n	n	а	ti	O	ľ	1

Description	Part Number	Α	В	С	D	E	Weight
1" Copper Manifold, 4 outlets (1/2")	Q2801050	8.95"	2.40"	1.50"	1/2"	N/A	0.80 lbs
1" Copper Manifold, 6 outlets (1/2")	Q2811050	11.95"	2.40"	1.50"	1/2"	N/A	1.10 lbs
1" Copper Manifold, 8 outlets (1/2")	Q2821050	14.95"	2.40"	1.50"	1/2"	N/A	1.40 lbs
1" Copper Manifold, 10 outlets (1/2")	Q2831050	17.95"	2.40"	1.50"	1/2"	N/A	1.70 lbs
1" Copper Manifold, 12 outlets (1/2")	Q2841050	20.95"	2.40"	1.50"	1/2"	N/A	1.90 lbs

Code Approvals/Standards

ANSI/NSF 14 and 61 certified ASTM F 877 ASTM F 1960 CAN/CSA B137.5 ICBO ER 5142 IPC UPC NSPC SBCCI (PST and ESI Report No. 9661) UL 1821

Installation

- Any product designed to mount one (1) inch copper pipe may be used as a mounting bracket
- Any bend within six (6) inches of the ProPEX connection to the manifold requires the use of a tube talon or bend support.
- Refer to the Wirsbo AQUAPEX Installation Handbook for additional information.

Related Applications

AQUAPEX — Hot and Cold Potable Water

