

ProPEX® LF Brass Ice Maker Valve

Submittal Information
Revision D: Feb. 22, 2018

Project information

Job name:

Location:

Part no. ordered:

Engineer:

Date submitted:

Contractor:


Submitted by:

Manufacturer's representative:

Approved by:

Technical data

Material:	C69300 LF Brass
Maximum temperature (no pressure):	250°F (121°C)
Maximum working pressure:	250 psi



Product information and application use

Uponor ProPEX® Lead-free (LF) Brass Ice Maker Valve connects ½" Uponor AquaPEX® tubing to ¼" O.D. compression with quarter-turn and shut-off capability.¹

✓ Description	Part number	A	B	Weight
ProPEX LF Brass Ice Maker Valve, ½" PEX x ¼" O.D. (angle)	LF4785025	2.75"	1.61"	0.30 lbs.
ProPEX LF Brass Ice Maker Valve, ½" PEX x ¼" O.D. (straight)	LF4786025	2.75"	1.61"	0.35 lbs.

Installation

Install valves according to local building code. Do not dismantle. Refer to the Uponor Professional Plumbing Installation Guide for additional information.

Standards

CSA B137.5 and B125; ASTM F877; ASTM F1960; ASME A112.18.1

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

IAPMO 3960; NSF 61- and 9-certified

Related applications

PEX-a plumbing systems

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
uponorpro.com

¹ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.